




# 短节距精密滚子链链轮

## Short pitch precision roller chain wheels


1"×5/8" 16A-1-2-3 GB1244-1997 DIN8187 ISO/R606	链轮齿部参数MM		
		节距	P
	滚子直径	d-φ	15.88
	元弧半径	r3	26
	倒角宽度	C	3.2
	齿宽	B1	14.6
	齿宽	b1	14.1
	齿宽	B2	43.4
	齿宽	B3	72.7



A型单排平片链轮  
A type simplex plate wheels



A型双排平片链轮  
A type duplex plate wheels



A型叁排平片链轮  
A type triplex plate wheels

齿数 Z	外径 de	节径 dp	单排链轮 Simplex			双排链轮 Duplex			叁排链轮 Triplex		
			dm	D1	A	dm	D2	A	dm	D3	A
8	77	66.37	42	16	35	42	20	65			
9	85	74.27	50	16	35	50	20	65			
10	93	82.19	55	16	35	56	20	65			
11	101.5	90.14	61	16	40	64	20	70			
12	109	98.14	69	16	40	72	20	70	52	25	100
13	117	106.12	78	16	40	80	20	70			
14	125	114.15	84	16	40	88	20	70			
15	133	122.17	92	16	40	96	20	70	96	25	100
16	141	130.2	100	20	45	104	25	70			
17	149	138.22	100	20	45	112	25	70	115	25	100
18	157	146.28	100	20	45	120	25	70			
19	165.2	154.33	100	20	45	128	25	70	128	25	100
20	173.2	162.38	100	20	45	130	25	70			
21	181.2	170.43	110	20	50	130	25	70	130	25	100
22	189.3	178.48	110	20	50	130	25	70			
23	197.5	186.53	110	20	50	130	25	70	130	25	100
24	205.5	194.59	110	20	50	130	25	70			
25	213.5	202.66	110	20	50	130	25	70			
26	221.6	210.72	120	20	50	130	25	70	130	25	100
27	229.6	218.79	120	20	50	130	25	70			
28	237.7	226.85	120	20	50	130	25	70			
29	245.8	234.92	120	20	50	130	25	70			
30	254	243	120	20	50	130	25	70			
31	262	251.08	120	25	50	140	25	70			
32	270	259.13	120	25	50	140	25	70			
33	278.5	267.21	120	25	50	140	25	70			
34	287	275.28	120	25	50	140	25	70			
35	296.2	283.46	120	25	50	140	25	70			
36	304.6	291.44	120	25	50	140	25	70			
37	312.6	299.51	120	25	50	140	25	70			
38	320.7	307.59	120	25	50	140	25	70			
39	328.8	315.67	120	25	50	140	25	70			
40	336.9	323.75	120	25	50	140	25	70			
42	353	339.89	120	25	50	140	25	70			
45	377.1	364.12	120	25	50	140	25	70			
50	417.4	404.52	130	30	50	140	25	70			
55	457.9	444.92	130	30	50	140	25	70			
60	498.3	485.33	130	30	50	140	25	70			

